

SN-258PLUS NEW-1

Product feature

- Multi-channel access with auto scan (240 channels)
- Multi-handset system (up to 15)
- Multi-base system (up to 4)
- Walkie-Talkie between handsets
- Half-DUPLEX group call
- Two-way paging and hands-free intercom
- 10-set memory dial 920 digits)
- Last number redial
- Tone/Pulse dialing model selectable
- Change channel during conversation
- Keypad lock function
- Flash time programmable
- Ring volume adjustable
- Voice volume adjustable
- Music on hold
- Touch any key answer
- Handset with power saving circuit
- Low battery alert and indicator
- Out of range alert
- Battery power status display
- Fast charge
- Built-in noise cancellation circuit(compander)
- Bulit-in voice security and mutation circuit (Scrambler)
- Auto answer and hang-up
- Transferring a call among handsets
- Hands-free kit for handset (optional)
- Separate charger(optional)
- Vibration alert (Vibration version only)

Specification

	Base station	Handset
Transmitter		
Frequency	388 MHz	262 MHz
Output power	1 W	350 m W

Spurious emission	55 dBc	55 dBc
Current consumption		
Stand-by	100 mA	7~12 mA
Talk	600 mA	350 mA
Receiver		
Frequency	262MHz	388MHz
Sensitivity at 12 dB SINAD (CCITT)	-122dBm	-122dBm
Adjacent channel rejection	50 dBc	50 dBc
Spurious response	55 dBc	55 dBc
Power source	AC 110V/60 Hz AC 220V/50 Hz DC 12V	4.8V/750 mAh Ni-Mh Battery
Dimension	L x W x H (m/m) 195x 145x 51	L x W x H (m/m) 150x 53x 32
Weight	500g	210g

Application

Ultra Long Communication Range

